



Updated June 2021

Product type

Storage controller in a Storage Shelf

Manufacturer's name, registered trade name, and registered address

NetApp
NetApp, Inc.
1395 Crossman Ave.
Sunnyvale, CA 94089
United States
+1 408-822-6000

Product model number

NAJ-1503

Marketing model Number

E2860, 2860, E5760, 5760, SG5760, SG6060*

*Applies to the Disk Shelf only. See SG6000-CN for the compute node data sheet.

First year of manufacture

2018

PSU efficiency

Load percentage	TDPS-2325AB A PSU efficiency
10%	81.64%
20%	91.94%
50%	94.38%
100%	93.35%
Average efficiency	93.22%
Power Factor at 50% load	0.990

Declared ASHRAE operating condition class

ASHRAE rating	A3
Operating temperature range	5 to 40 degrees C
Recommended operating range	18 to 27 degrees C
Allowable operating relative humidity	-12°C DP and 8% to 24°C DP and 85%
Recommended operating relative humidity	-9°C DP to 15°C DP and 60%
Maximum Dew Point	24
Maximum rate of change (°C/hr)	5/20

Material ease of disassembly for repair or reuse

E-Series: <https://docs.netapp.com/ess-11/index.jsp> in the System maintenance tab

Neodymium in HDDs

All 10K RPM and 15K RPM drives have less than 5 g

All 7200 RPM drives have between 5g and 25g

Cobalt in Li-Ion Batteries

All Li-Ion Cells have less than 5g



All Li-Ion Battery Packs have between 5g and 25g

Secure data deletion information: E-series

E-series secure data deletion capability is provided by a Python script which will issue commands appropriate for the drives in the array configuration to eliminate all user data.

Minimum SANtricity OS (controller software) level required is **11.70.1**.

The script can be downloaded at this location:

<https://mysupport.netapp.com/site/products/all/details/eseries-santricity/downloads-tab/download/62736/SecDel2020/downloads>

To run the script, a host (Linux or Windows) is required, with the following connectivity and components:

- Network connectivity to the array
- Python 3.6 with the 'requests' library