



Lithium Battery Safety Document – Section II or Section IB Shipments

AWB or Tracking Number: _____

This document may be used to comply with the additional documentation requirements of the IATA DGR.

WARNING: LITHIUM BATTERIES THAT HAVE BEEN RECALLED BY THE MANUFACTURER FOR SAFETY REASONS **MUST NOT** BE SHIPPED BY AIR.

Terminology:

- Cell – *electrochemical unit, consisting of an anode and a cathode, capable of generating electrical current*
- Battery – *assembly of cells*
- Lithium ion cells/batteries – *generally rechargeable – includes lithium polymer cells/batteries*
- Lithium metal cells/batteries – *non-rechargeable*

This shipment contains lithium cells or batteries in the following configuration (check applicable description):

Lithium Ion - Maximum of • 20 Watt-hours per cell or • 100 Watt-hours per battery	Lithium Metal – Maximum of • 1 gram of lithium metal per cell or • 2 grams of lithium metal per battery
☐ Cells or batteries only (Lithium ion batteries in compliance with Section II of PI 965, UN 3480) - <i>Cells or batteries in a package, without electronic equipment:</i> Package Limit: ≤2.7 Wh = 2.5 kg; <u>or</u> >2.7 Wh but ≤ 20 Wh = 8 cells; <u>or</u> >2.7 Wh but ≤ 100 Wh = 2 batteries	☐ Cells or batteries only (Lithium metal batteries in compliance with Section II of PI 968, UN 3090) - <i>Cells or batteries in a package, without electronic equipment.</i> Package Limit: ≤0.3 g = 2.5 kg; <u>or</u> >0.3 g but ≤ 1 g = 8 cells; <u>or</u> >0.3 g but ≤ 2g = 2 batteries
☒ Cells or batteries only (Lithium ion batteries in compliance with Section IB of PI 965, UN 3480) - <i>Cells or batteries in a package, without electronic equipment</i> <i>Packages must be limited to 10 kg net weight of batteries.</i>	☐ Cells or batteries only (Lithium metal batteries in compliance with Section IB of PI 968, UN 3090) - <i>Cells or batteries in a package, without electronic equipment</i> <i>Packages must be limited to 2.5 kg net weight of batteries..</i>
☐ Packed with equipment (Lithium ion batteries in compliance with Section II of PI 966, UN 3481) - <i>Cells or batteries contained in a package with associated electronic equipment.</i> <i>Packages must be limited to 5 kg net weight of batteries.</i>	☐ Packed with equipment (Lithium metal batteries in compliance with Section II of PI 969, UN 3091) - <i>Cells or batteries contained in a package with associated battery-powered equipment – with the batteries not installed in the equipment.</i> <i>Packages must be limited to 5 kg net weight of batteries.</i>
☐ Contained in equipment (Lithium ion batteries in compliance with Section II of PI 967, UN 3481) - <i>Cells or batteries installed in equipment.</i> <i>Packages must be limited to 5 kg net weight of batteries.</i>	☐ Contained in equipment (Lithium metal batteries in compliance with Section II of PI 970, UN 3091) - <i>Cells or batteries installed in equipment.</i> <i>Packages must be limited to 5 kg net weight of batteries.</i>

- This package must be handled with care. A flammability hazard exists if the package is damaged.
- If this package is damaged in transportation, it must not be loaded until the condition of the contents can be verified. The batteries contained in this package must be inspected for damage and may only be repacked if they are intact and protected against short circuits.
- For more information about the batteries contained in this package, call the following telephone number:

CHEMTREC for Lithium Battery Information Number:

For EMERGENCY information call 800-424-9300 or outside the United States call 703-527-3887



210-06806+A1

Printed in USA

	Document Name: 4465_Safety Data Sheet	Rev.
	Page 1 of 7	03

File Number: SDS_4465_QX_2025_R01
Date: 2025-01-01

Section 1 -- Product and Company Identification

Product Name: Rechargeable Li-ion Battery

Product Model No.: 271-00029

Inventus Part No: 4465

COMPANY NAME:

Inventus Power, Inc.

1200 Internationale Parkway, Woodridge IL 60517

EMERGENCY TELEPHONE NUMBER:

Inside the US: 1-800-424-9300

Outside the US: 1-703-527-3887

MANUFACTURING SITE:

Name: ICC Electronics (Dongguan) Ltd.

Address1: No.23, Shang Yuan Road, QingXi Town, Dongguan City, Guangdong Province, China

Telephone number: +86 769 87731085

Emergency telephone number: +86 769 87731085

Section 2 -- Composition / Information on Ingredients

Battery Product Matrix:

Inventus Power P/N	Customer P/N	Pack Configuration	Pack Nominal Voltage V	Pack Nominal Capacity (Ah)	Pack Energy (Wh)
4465	271-00029	2S1P	7.2	2.9	20.9



210-06813+F0

Printed in USA

One Team, Safety Data Sheet - A

Battery Chemical Composition:

Component	Material	Formula	CAS Number	Percentage range (wt %)
Positive Electrode	Lithium Nickel Cobalt manganese Oxide	LiNiMnCoO ₂	182442-95-1	25~33%
Negative Electrode	Graphite	C	7440-44-0	15~25%
Electrolyte	Ethylene Carbonate	C ₃ H ₄ O ₃	96-49-1	2~5%
	Diethyl Carbonate	C ₅ H ₁₀ O ₃	105-58-8	2~5%
	Lithium Hexafluorophosphate	LiPF ₆	21324-40-3	15-22%
Outer case	Aluminium	Al	7429-90-5	5%
	Copper	Cu	7440-50-8	5%
	Iron	Fe	7439-89-6	5%

Section 3-- Hazards Identification

Under normal usage, there is no contact with electrolyte and no hazard exists. Abusive conditions such as crush, severe drop, puncture etc. must be avoided as that can lead to fire and explosion of the battery. If exposed to high temperature or fire, cell may leak electrolyte and in extreme cases explode. The vented gas may contain among others Hydrogen Fluoride.

The information in this section relates to unusual conditions resulting from abuse in which the battery electrodes and electrolytes are exposed.

Most severe hazard present in case of fire. Fire can cause explosion, exposure to toxic fume/Vapor

i. GHS Classification

Skin irritation	(Category 2)
Skin sensitization	(Category 1)
Eye irritation	(Category 2)
Single target organ, toxicity, single exposure	(Category 3)
Carcinogen	(Category 1B)

ii. GHS Label elements, including precautionary statements

Pictograms



Signal word

Danger/Warning

	Document Name: 4465_Safety Data Sheet	Rev.
	Page 3 of 7	03

iii. Hazard statements

H315 Causes skin irritation in case of breach of battery casing

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation in case of leak or spill of electrolyte, again under abuse conditions

H335 May cause respiratory irritation when exposed to fumes from fire, but not under normal usage conditions

R10 Flammable

iv. Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection / face protection.

P312 Call a POISON CENTER or doctor/ physician if exposed to fumes or electrolyte

P313 Get Medical Attention

P302 + P350 IF ON SKIN: Gently wash with plenty of soap and water.

P301 + P330 + P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Section 4 -- First Aid

Under normal operating condition, contents of the cells are in sealed (polymer pouch/metal can or cylinder) condition and pose no threat to the user.

Exposure to the cell internal content happens under abusive conditions.

Inhalation: Contents of open battery may cause respiratory irritation. Move to fresh air immediately and seek medical attention.

Skin: Contents of open battery may cause skin irritation. Wash skin with copious amount of soap and water.

Eye: Contents of open battery may cause eye irritation. Flush eyes immediately with water for at least 15 minutes and seek medical attention.

Ingestion: Seek medical attention immediately. Induce vomiting.

Section 5 -- Fire Fighting

In case of Fire use CO2 or CLASS ABC fire extinguisher

In case battery burns with other combustible, use corresponding fire extinguisher. Corrosive fumes may be present during fire. Use protective equipment (gloves, breathing apparatus, goggles etc.)

Gases from the burning fire will include Hydrogen Fluoride, Carbon oxides, Hydrocarbons among others.

Section 6 -- Accidental Release

Battery material is enclosed in either metal casing or in laminate and does not release easily under normal usage. Under abuse condition such as puncture, high heat exposure, electrical abuse electrolyte containing vinyl chloride salt in organic solvent may leak out. See section 4 for first aid measure. Seek medical attention.

Contain the spillage with sand or vermiculite and if necessary bunding.

Do not dispose of spillage waste into regular waste stream.

Section 7 -- Instructions on Safe Handling and Use

Storage: Store within the recommended temperature limit of the battery (read instruction manual for specific limits). Do not expose to high temperature (60°C/140°F). Avoid short circuit of the battery. Short circuit of the battery may cause release of gas and may pose burn hazard.

Handling: Do not disassemble, crush, or otherwise abuse the battery. Do not open the battery.

Charge: Charge only with dedicated/specific chargers designed for this battery

Discharge: Discharge within the temperature limits of the battery detailed in the specification.

Disposal: Dispose/Recycle according to the applicable municipal, state, and federal regulations. Do not dispose in household or commercial waste bin.

Caution: This battery when abused may pose fire, explosion, and severe burn hazard. Handle with caution.

Section 8 -- Exposure Control and Special Protection Information

Control Parameters:

Components with workplace controls:

Graphite CAS 7782-42-5	TWA	2.5 mg/m ³	USA, NIOSH recommended exposure limits
		5 mg/m ³	USA, OSHA limits for air contaminants
		5 mg/m ³	USA, OSHA occupational exposure limits
		3 mg/m ³	Australian workplace exposure standards for airborne contaminants
	TWA	2 mg/m ³	Canada, British Columbia OEL
			Canada, Alberta OEL
	TWAEV	5 mg/m ³	Canada, Quebec OELs
	TWA	2.5 mg/m ³	USA, OSHA limits for air contaminants
			USA, OSHA occupational exposure limits
		2.5 mg/m ³	USA, ACGIH Threshold Limit Value
		2.5 mg/m ³	Australian workplace exposure standards for airborne contaminants
Lithium CAS 21324-40-3 hexafluorophosphate	TWA	2.5 mg/m ³	Canada, British Columbia OEL Canada, Alb. OEL
	TWAEV	2.5 mg/m ³	Canada, Quebec OELs

Engineering Controls:

Have eye bath available.

Use non-sparking tools.

Protective Equipment: Wear chemical-resistant gloves and chemical safety goggles.

Hygiene: Follow good industrial hygiene procedures. Keep away from food, beverages.

Use safety precautions for handling high voltage, high wattage battery.

Use safety goggles, acid resistant safety gloves, air mask if exposed to internal content of the cell/battery.

Section 9 -- Physical and Chemical Properties

Appearance: Solid

Form Factor: Mostly rectangular

Odor: N/A

PH: N/A

Flash Point: N/A

Density: N/A

Solubility: Insoluble in Water

Section 10 -- Stability and Reactivity

Not reactive under normal condition of usage.

Note safe handling procedure.

Avoid high temperature, high humidity and mechanical abuse, short circuit, and sparks

Read label and manufacturer instruction before usage and disposal

Section 11 -- Toxicological Effect

Acute Toxicity:

Not known for Lithium Cobaltate, Aluminum, and Graphite or Lithium Iron Phosphate.

Copper causes gastrointestinal disturbance in 60-100mg sized coarse particulate. TDLo- Rabbit 375mg/kg

Organic electrolyte LD50, oral - -Rat 2000mg/kg or more

Local Effects:

Not known for Lithium Cobaltate, Graphite and Organic Electrolyte or Lithium Phosphate.

Aluminum has no known local effects.

Copper in coarse particulate is eye irritant

No known carcinogen in this product.

Section 12 -- Ecological Information

Battery is not biodegradable. Do not dispose in landfill. Please follow local regulations regarding recycle and disposal.

No data available on aquatic toxicity, Bio accumulative potential, Mobility in soil.

Section 13 -- Disposal Information

Dispose/Recycle according to the applicable municipal, state, and federal regulations. Do not dispose in household or commercial waste bin or stream. Battery label contains Eu Battery directive compliant marking. Follow local and federal regulations for disposal and recycle of lithium-ion batteries.

Section 14 -- Transportation Information

Proper Shipping Name: Lithium-Ion Batteries.

The UN number for the battery pack is UN3480, and it also can be UN3481 when the battery pack is contained in the equipment or packed with the equipment.

The battery meets the requirements of the test in the United Nations (UN) Manual of Tests and Criteria, Part III, sub-section 38.3

DOT: Refer to Attachment ERG 2024 guide 147 (Lithium-Ion battery Guide)

IMDG: Refer to IMDG/Ocean Transport ENS F-A, S-I

IATA: Refer to IATA-ICAO/Air Transport ERG CODE 12FZ

When large number of batteries are transported by ship, vehicle and railroad, avoid high temperature and dew condensation.

Avoid transportation which may cause damage of package.

Section 15 -- Regulatory Information

This product is considered an article under the chemical inventories listed below and consequently is exempt from listing on these inventories:

- US EPA Toxic Substance Control Act (TSCA)
- European Inventory of Existing Chemical Substances (EINECS/ELINCS)
- Other International Regulations

Transport of rechargeable lithium-ion batteries is regulated by various bodies, (IATA, IMO, US-DOT) that follow the United Nations "Recommendations on the Transport of Dangerous Goods.

Regulations specifically applicable to the product:

ICAO 2025/2026 Edition of ICAO Technical Instructions for the Safety Transport of Dangerous Goods by Air
IMO IMDG Amendment 41-22 2022 Edition. battery pack complies with the special provision 188 of the IMDG CODE.

	Document Name: 4465_Safety Data Sheet	Rev.
	Page 7 of 7	04

IATA 66th Edition (2025) of the IATA Dangerous Goods Regulations (DGR),
US Department of Transportation DOT (49 CFR 100-185), (USA)
OSHA hazard communication standard (29 CFR 1910.1200)

The battery is complied with the requirements of PI965, IB for Packs <100Wh
Batteries shipped with or contained in equipment must follow IATA Packing Instruction 966, Section II or PI967, Section II.
Shipment must accompany dangerous goods shipping paper.
Employees handling lithium-ion batteries must receive dangerous goods/hazmat training.

Section 16 -- Other Information

The information contained in this Safety data sheet is based on the present state of knowledge and current legislation.
This safety data sheet provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for applications.
Although the electrolyte contains chemicals that by itself can cause harm, it is not present in an amount or form to cause splash.

UN38.3 Lithium Battery(Cell) Test Summary

UN38.3 锂电池(电芯)试验概要

No. : RZUN2017-3988-M1-TS

Cell or Battery Information 电池/电芯信息		
Name 名称:	Rechargeable Lithium-ion Battery/可充电锂离子电池	
Type/Model 型号:	271-00029 7.2V 2.9Ah 20.9Wh	
Color 颜色:	White/白色	
Shape 形状:	Prismatic/棱柱形	
Completed Battery/Cell Mass 电池/电芯整体质量	110.1g	
☒	Belongs to Lithium-ion Battery, the Wh rating is 属于锂离子电池/电芯, 瓦时数为	20.9Wh
☐	Belongs to Lithium metal Battery, the Lithium content is 属于锂金属电池/电芯, 锂金属含量为	

Manufacturer Information 制造商信息		
Manufacturer: 制造商:	ICC Electronics (Dongguan) Ltd. / Fabricators International Ltd. 辉碧电子(东莞)有限公司	
Address: 地址:	No.23, Shangyuan Road, Qingxi Town, Dong Guan City, Guangdong, P. R. China 广东省东莞市清溪镇上元路 23 号	
Telephone 电话:	020-39298880-6800	Email 电邮: andy.quan@inventuspower.com
Website 网址:	www.inventuspower.com	

Laboratory Information 检测实验室信息		
Laboratory: 检测实验室:	Vkan Certification & Testing Co., Ltd. 威凯检测技术有限公司	
Address: 地址:	No.3,Tiantaiyi Road, Kaitai Avenue, Science City, Guangzhou P. R. China. 中国 广州市科学城开泰大道天泰一路 3 号	
Tel 电话:	86-020-32293888	Email 电邮: office@cvc.org.cn
		Website 网址: http://www.cvc.org.cn

UN38.3 Test conducted and results UN38.3 试验项目和结果		
Test Report ID 检测报告编号:	RZUN2017-3988-M1	Date of Test Report 检测报告签发日期: 2019-01-23
Manual of Test and Criteria version / amendment: 试验和标准手册版本号/修订版:	ST/SG/AC.10/11/Rev.6/Section 38.3	

List of Tests Completed 已完成的试验项目清单			
Test Items 试验项目	Pass 通过	Fail 失败	Reference to assembled battery testing requirement: 关于组合电池的试验要求:
☒ T1 Altitude Simulation 高度模拟	☒	☐	☒ Not applicable 不适用
☒ T2 Thermal Test 热冲击	☒	☐	☐ Applicable, reference to 38.3.3 (f) 适用于 38.3.3 (f)
☒ T3 Vibration 振动	☒	☐	☐ Applicable, reference to 38.3.3 (g) 适用于 38.3.3 (g)
☒ T4 Shock 冲击	☒	☐	Other executive standards/其他执行标准:
☒ T5 External Short Circuit 外部短路	☒	☐	
☒ T6 Impact/ Crush 撞击/ 挤压	☒	☐	
☒ T7 Overcharge 过充电	☒	☐	
☒ T8 Forced Discharge 强制放电	☒	☐	

Note: The test results of this summary are only valid for the tested samples listed in test report RZUN2017-3988-M1.

注: 此摘要的测试结果仅对测试报告 RZUN2017-3988-M1 中列出的测试样品有效


Title/职务: Manager/经理

Signatory/签发人:

黄 强

Stamp of CVC

CVC 印章:



210-06689+C1

Printed in USA

LTC-R-4279-UN38.3-A2