



Updated June 2021

Product type

Storage controller in a Storage Shelf

Manufacturer's name, registered trade name, and registered address

NetApp
NetApp, Inc.
1395 Crossman Ave.
Sunnyvale, CA 94089
United States
+1 408-822-6000

Product model number

NAJ-1801

Marketing model Number

EF600, EF300

First year of manufacture

2019

PSU efficiency

Load percentage	DPS-1600AB-18 PSU efficiency	PS-2162-8F
10%	89.50%	89.28%
20%	92.93%	92.67%
50%	94.37%	94.41%
100%	92.71%	97.70%
Average efficiency	93.84%	93.28%
Power Factor at 50% load	0.980	0.990

Declared ASHRAE operating condition class

ASHRAE rating	A2
Operating temperature range	10 to 35 degrees C
Recommended operating range	18 to 27 degrees C
Allowable operating relative humidity	-12°C DP and 8% to 21°C DP and 80%
Recommended operating relative humidity	-9°C DP to 15°C DP and 60%
Maximum Dew Point	21
Maximum rate of change (°C/hr)	5/20

Material ease of disassembly for repair or reuse

E-Series: <https://docs.netapp.com/ess-11/index.jsp> in the System maintenance tab

Neodymium in HDDs

All 10K RPM and 15K RPM drives have less than 5 g

All 7200 RPM drives have between 5g and 25g

Cobalt in Li-Ion Batteries

All Li-Ion Cells have less than 5g



All Li-Ion Battery Packs have between 5g and 25g

Secure data deletion information: E-series

E-series secure data deletion capability is provided by a Python script which will issue commands appropriate for the drives in the array configuration to eliminate all user data.

Minimum SANtricity OS (controller software) level required is **11.70.1**.

The script can be downloaded at this location:

<https://mysupport.netapp.com/site/products/all/details/eseries-santricity/downloads-tab/download/62736/SecDel2020/downloads>

To run the script, a host (Linux or Windows) is required, with the following connectivity and components:

- Network connectivity to the array
- Python 3.6 with the 'requests' library